

Black Hills Bentonite LLC Bentonite Plug 3/8 or 3/4" Chips Safety Data Sheet

Revision Date: 12/31/22 Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier
Product Form: Mixture

Product Name: Bentonite Plug 3/8 or 3/4" Chips

Synonyms: Montmorillonite

Intended Use of the Product

Sealing of abandoned water wells, drill holes, and monitor well casing.

Can also be used for sealing animal stock tanks, irrigation ditches and seismic shot holes.

Responsible Party Contact Information

Black Hills Bentonite LLC PO Box 9

Mills, WY 82644 307-265-3740

customerservice@bhbbentonite.com

Emergency Telephone Number Emergency Number: 307-234-6470

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315 Eye Dam. 1 H318 Carc. 1A H350 STOT RE 1 H372

Full text of H-phrases: see section 16

Label Elements GHS-USLabeling

Hazard Pictograms (GHS-US)

GH SO

Signal Word (GHS-US)

Hazard Statements (GHS-US)

Danger

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements (GHS-US)

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink, or smoke when using this product.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for 3-10 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

Black Hills Bentonite LLC

Safety Data Sheet

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. If involved in a fire or other decomposition occurs corrosive, toxic, and acrid vapors may be released.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Silica, amorphous	(CAS No) 7631-86-9	38.4 - 66	Not classified
Water	(CAS No) 7732-18-5	8 - 20	Not classified
Aluminum oxide (Al2O3), hydrate	(CAS No) 1333-84-2	10.56 - 19	Not classified
Quartz	(CAS No) 14808-60-7	1-5	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Iron oxides	(CAS No) 1332-37-2	1.5 - 4.5	Not classified
Sodium oxide (Na2O)	(CAS No) 1313-59-3	0.9 - 1, 1 - 3.5	Skin Corr. 1B, H314 Eye Dam. 1, H318
Calcium oxide	(CAS No) 1305-78-8	0.3 - 1, 1 - 2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Magnesium oxide (MgO)	(CAS No) 1309-48-4	0.48 - 2	Not classified
Silica, cristobalite	(CAS No) 14464-46-1	0.1 - 1	Carc. 1A, H350 STOT RE 1, H372
Tridymite	(CAS No) 15468-32-3	0.1 - 1	Carc. 1A, H350 STOT RE 1, H372
Potassium oxide	(CAS No) 12136-45-7	0.12 - 0.7	Skin Corr. 1C, H314 Eye Dam. 1, H318
Titanium dioxide	(CAS No) 13463-67-7	0.06 - 0.1, 0.1 - 0.2	Carc. 2, H351

Full text of H-phrases: see section 16

More than one of the ranges of concentration prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Flush with plenty of water for at least 3-10 minutes. Seek medical advice if irritation develops or persists. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 3-10 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.

Ingestion: Do not induce vomiting. Rinse mouth. Seek medical attention if any problems arise.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. Causes skin irritation. May cause cancer. Repeated or prolonged inhalation may damage lungs. **Inhalation:** May cause respiratory irritation. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

Skin Contact: Causes skin irritation. Symptoms may include redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Causes serious eye damage. Symptoms may include redness, pain, swelling, itching, burning, tearing, and blurred vision

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Black Hills Bentonite LLC 2/13

Safety Data Sheet

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Alcohol-resistant foam. Dry chemical. Carbon dioxide. Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising from the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Reacts with water. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire areas without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: May release corrosive vapors. May liberate toxic gases.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Use safe, appropriate measures.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. **Emergency Procedures:** Eliminate ignition sources. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers. Water.

Specific End Use(s)

Sealing of abandoned water wells, drill holes, and monitor well casing. For sealing animal stock tanks, irrigation ditches and seismic shot holes.

Black Hills Bentonite LLC 3/13

Safety Data Sheet

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Silica, amorphous (7631-86-	9)	
USAOSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	20 MPPCF (80mg/m³/%SiO)
Nunavut	OEL TWA (mg/m³)	2 mg/m³ (respirable mass)
		5 mg/m³ (total mass)
		0.05 mg/m³ (regulated under Silica flour-respirable mass)
		0.15 mg/m³ (regulated under Silica flour, total mass)
Northwest Territories	OELTWA (mg/m³)	2 mg/m³ (respirable mass)
		5 mg/m³ (total mass)
		0.05 mg/m³ (regulated under Silica flour-respirable mass)
		0.15 mg/m³ (total mass, regulated under Silica flour)
Yukon	OEL TWA (mg/m³)	300 particle/mL (as measured by Konometer
		instrumentation)
		20 MPPCF (as measured by Impinger instrumentation)
		2 mg/m³ (respirable mass)
Iron oxides (1332-37-2)	ACCILLTA/A (mg/m³)	Γ mα/m³
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	10 mg/m³ Iron Oxide fume
Nunavut	OEL STEL (mg/m³)	10 mg/m³ (fume)
Nunavut Northwest Territories	OEL TWA (mg/m³) OEL STEL (mg/m³)	5 mg/m³ (fume) 10 mg/m³ (fume)
	, ,	
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³ (fume)
Magnesium oxide (MgO) (13		10/3/6
Mexico	OEL TWA (mg/m³)	10 mg/m³ (fume)
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (fume, total particulate)
USA IDLH Alberta	US IDLH (mg/m³) OEL TWA (mg/m³)	750 mg/m³ (fume) 10 mg/m³ (fume)
	· - ·	10 mg/m² (respirable dust and fume)
British Columbia	OEL STEL (mg/m³)	
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume)
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
New Brunswick	OELTWA (mg/m³)	10 mg/m³ (fume)
Newfoundland & Labrador	OELTWA (mg/m³)	10 mg/m³ (inhalable fraction)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (fume)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (fume)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (fume)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (fume)
Ontario	OELTWA (mg/m³)	10 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Québec	VEMP (mg/m³)	10 mg/m³ (fume)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)

Black Hills Bentonite LLC 4/13

Safety Data Sheet

OEL STEL (mg/m³)	10 mg/m³ (fume)	
	10 mg/m³ (fume)	
OELTWA (mg/m³)	2 mg/m³	
	2 mg/m ³	
	5 mg/m³	
	2 mg/m³	
US IDLH (mg/m³)	25 mg/m ³	
OEL TWA (mg/m³)	2 mg/m ³	
OEL TWA (mg/m³)	2 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL STEL (mg/m³)	4 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL STEL (mg/m³)	4 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
OELTWA (mg/m³)	2 mg/m³	
VEMP (mg/m³)	2 mg/m³	
OEL STEL (mg/m³)	4 mg/m³	
, . ,	2 mg/m³	
	4 mg/m³	
OEL TWA (mg/m³)	2 mg/m³	
7)		
	10 mg/m³	
	20 mg/m ³	
,,	10 mg/m ³	
<u> </u>	Not Classifiable as a Human Carcinogen	
, ,, ,, ,	15 mg/m³ (total dust)	
, 5. ,	5000 mg/m ³	
,,	10 mg/m³	
OELTWA (mg/m³)	10 mg/m³ (total dust)	
051 5044 (2)	3 mg/m³ (respirable fraction)	
	10 mg/m ³	
· - ·	10 mg/m³	
	10 mg/m³	
	10 mg/m ³	
OEL IWA (mg/m³)	5 mg/m³ (respirable mass) 10 mg/m³ (total mass)	
OEL TWA (mg/m³)	5 mg/m³ (respirable mass) 10 mg/m³ (total mass)	
OEL TWA (mg/m³)	10 mg/m³	
OEL TWA (mg/m³)	10 mg/m³	
OEL IWA (mg/m²)		
, ,	<u> </u>	
VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline	
VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline silica-total dust)	
, ,	10 mg/m³ (containing no Asbestos and <1% Crystalline	
	OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) OEL STEL (TWA) (mg/m³) OEL STEL (TWA) (mg/m³) OEL TWA (mg/m³)	

Black Hills Bentonite LLC 5/13

Safety Data Sheet

	200	-
Yukon	OELTWA (mg/m³)	30 MPPCF
		10 mg/m ³
Silica, cristobalite (14464-46	-	
Mexico	OELTWA (mg/m³)	0.05 mg/m³ (respirable fraction)
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen
USANIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)
USAIDLH	US IDLH (mg/m³)	25 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nunavut	OELTWA (mg/m³)	0.05 mg/m³ (respirable mass) 0.15 mg/m³ (total mass)
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m³ (respirable mass) 0.15 mg/m³ (total mass)
Ontario	OEL TWA (mg/m³)	0.05 mg/m³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Québec	VEMP (mg/m³)	0.05 mg/m³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	150 particle/mL
Tridymite (15468-32-3)		
Mexico	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)
USAIDLH	US IDLH (mg/m³)	25 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)
New Brunswick	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	0.05 mg/m³ (respirable mass) 0.15 mg/m³ (total mass)
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m³ (respirable mass) 0.15 mg/m³ (total mass)
Québec	VEMP (mg/m³)	0.05 mg/m³ (respirable dust)
Yukon	OELTWA (mg/m³)	150particle/mL
Quartz (14808-60-7)	: - <i>'</i>	·
Mexico	OEL TWA (mg/m³)	0.1 mg/m³ (respirable fraction)
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcino gen
USA OSHA	OSHA PEL (STEL) (mg/m³)	250 MPPCF/%SiO +5, 10mg/m / SiO +2
USANIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)
USAIDLH	US IDLH (mg/m³)	50 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)
British Columbia	OELTWA (mg/m³)	0.025 mg/m³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Nunavut	OEL TWA (mg/m³)	0.1 mg/m³ (respirable mass) 0.3 mg/m³ (total mass)
Northwest Territories	OELTWA (mg/m³)	0.1 mg/m³ (respirable mass)

Black Hills Bentonite LLC 6/13

Safety Data Sheet

Ontario	OEL TWA (mg/m³)	0.10 mg/m³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m³ (respirable fraction)
Québec	VEMP (mg/m³)	0.1 mg/m³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	300 particle/mL

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Suitable materials with adequate protection.

Hand Protection: Wear protective gloves. Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator whenever exposure may exceed established Occupational Exposure

Limits.

Environmental Exposure Controls: Do not allow the product to be released into rivers streams, or local sewage systems.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Solid

Appearance Grey Powder Odor Earthy **Odor Threshold** Not available

9 - 11

рΗ

Not available **Evaporation Rate Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available **Flash Point** Not available Not available **Auto-ignition Temperature Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20 °C Not available **Relative Density** Not available

Specific Gravity 2.65

Solubility Water: Insoluble Partition Coefficient: N-Octanol/Water Not available Not available Viscosity

Explosion Data – Sensitivity to Mechanical Impact Not expected to present an explosion hazard due to mechanical impact Explosion Data - Sensitivity to Static Discharge Not expected to present an explosion hazard due to static discharge

7/13 Black Hills Bentonite LLC

Safety Data Sheet

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with water. Hazardous reactions may occur on contact with certain chemicals. Refer to incompatible materials.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

<u>Possibility of Hazardous Reactions</u>: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong oxidizers. Water.

Hazardous Decomposition Products: The decomposition products are corrosive and hazardous to health.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation

pH: 9 - 11

Serious Eye Damage/Irritation: Causes serious eye damage

pH: 9 - 11

Respiratory or Skin Sensitization: Not classified **Germ Cell Mutagenicity:** Not classified

Teratogenicity: Not classified **Carcinogenicity:** May cause cancer

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss

Symptoms/Injuries After Skin Contact: Causes skin irritation. Symptoms may include redness, pain, swelling, itching, burning, dryness, and dermatitis

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Symptoms may include redness, pain, swelling, itching, burning, tearing, and blurred vision

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects

Chronic Symptoms: May cause cancer. May cause damage to organs through prolonged or repeated exposure. Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Silica, amorphous (7631-86-9)	
LD50 Oral Rat	>5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.2 mg/l (Exposure time: 1 h)
Calcium oxide (1305-78-8)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	>10000 mg/kg
Quartz (14808-60-7)	
LD50 Oral Rat	>5000 mg/kg
LD50 Dermal Rat	>5000 mg/kg

Black Hills Bentonite LLC 8/13

Safety Data Sheet

Silica, amorphous (7631-86-9)	
IARC Group	3
Titanium dioxide (13463-67-7)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Silica, cristobalite (14464-46-1)	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Tridymite (15468-32-3)	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Silica, amorphous (7631-86-9)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachy danio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
Calcium oxide (1305-78-8) LC50 Fish 1	1070 mg/l (Exposure time: 96 h - Species: Cyprinus Carpio [static])

Persistence and Degradability Not available

Bio accumulative Potential

Silica, amorphous (7631-86-9)	
BCF Fish 1	No bioaccumulation expected
Calcium oxide (1305-78-8)	
BCF Fish 1	No bioaccumulation
Disodium carbonate (497-19-8)	
BCF Fish 1	No bioaccumulation

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, territorial, provincial, and international regulations.

Ecology – Waste Materials: Avoid release to rivers, streams, and local sewer systems.

Black Hills Bentonite LLC 9/13

Safety Data Sheet

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport In

Accordance with IMDG Not regulated for transport In

Accordance with IATA Not regulated for transport In

Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Bentonite Plug 3/8 or 3/4" Chips		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Silica, amorphous (7631-86-9)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
Iron oxides (1332-37-2)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
Magnesium oxide (MgO) (1309-48-4)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
Calcium oxide (1305-78-8)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Potassium oxide (12136-45-7)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Sodium oxide (Na2O) (1313-59-3)		
Listed on the United States TSCA (Toxic Substances Control Act) in	,	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Titanium dioxide (13463-67-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
Water (7732-18-5)		
Listed on the United States TSCA (Toxic Substances Control Act) in	nventory	
Silica, cristobalite (14464-46-1)		
Listed on the United States TSCA (Toxic Substances Control Act) in	·	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
Tridymite (15468-32-3)		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
Quartz (14808-60-7)		
Listed on the United States TSCA (Toxic Substances Control Act) in	· ·	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	

US State Regulations

Titanium dioxide (13463-67-7)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.

Black Hills Bentonite LLC 10/13

Safety Data Sheet

Quartz (14808-60-7)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Silica, amorphous (7631-86-9)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium oxide (1305-78-8)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Potassium oxide (12136-45-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

Titanium dioxide (13463-67-7)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Silica, cristobalite (14464-46-1)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Tridymite (15468-32-3)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Quartz (14808-60-7)

- U.S. Massachusetts Right to Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Canadian Regulations

Bentonite Plug 3/8 or 3/4" Chips

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Class E - Corrosive Material



Silica, amorphous (7631-86-9)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

Misclassification Uncontrolled product according to WHMIS classification criteria

Aminoxide (Al2O3), hydrate (1333-84-2)

Listed on the Canadian DSL (Domestic Substances List)

Black Hills Bentonite LLC 11/13

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Iron oxides (1332-37-2)		
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Magnesium oxide (MgO) (1	309-48-4)	
Listed on the Canadian DSL		
Listed on the Canadian IDL ((Ingredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Calcium oxide (1305-78-8)		
Listed on the Canadian DSL	, , , , , , , , , , , , , , , , , , ,	
Listed on the Canadian IDL ((Ingredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class E - Corrosive Material	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Potassium oxide (12136-45-	•	
Listed on the Canadian DSL (·	
WHMIS Classification	Class E - Corrosive Material	
Sodium oxide (Na2O) (1313	-59-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class E - Corrosive Material	
Titanium dioxide (13463-67	-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Water (7732-18-5)		
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Silica, cristobalite (14464-4	6-1)	
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Tridymite (15468-32-3)		
Listed on the Canadian IDL (I	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Quartz (14808-60-7)		
Listed on the Canadian DSL		
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
This product has been class	sified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS	
contains all the information required by CPR.		

Black Hills Bentonite LLC 12/13

Safety Data Sheet

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date 12/31/22

Other Information This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

-
Acute toxicity (oral) Category 4
Carcinogenicity Category 1A
Carcinogenicity Category 2
Serious eye damage/eye irritation Category 1
Serious eye damage/eye irritation Category 2A
Skin corrosion/irritation Category 1B
Skin corrosion/irritation Category 1C
Skin corrosion/irritation Category 2
Specific target organ toxicity (repeated exposure) Category 1
Specific target organ toxicity (single exposure) Category 3
Harmful if swallowed
Causes severe skin burns and eye damage
Causes skin irritation
Causes serious eye damage
Causes serious eye irritation
May cause respiratory irritation
May cause cancer
Suspected of causing cancer
Causes damage to organs through prolonged or repeated exposure

Party Responsible for the Preparation of This Document

Black Hills Bentonite LLC

307-265-3740

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety, and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

Black Hills Bentonite LLC